

The STEAMFORCE® Range

Powerful Professional Steam Cleaning

SF

SteamForce 10 M6056

Area Specific Stand Operating Procedures (SOPs) on request

Making light work of heavy cleaning tasks

- * Mains water connection for nonstop cleaning power
- * Features steam volume regulator & front locking castor wheels
- * Produces 200 grams of dry steam per minute
- * Industrial quality steam socket and accessories
- * Optional Vac Kit (M7005) for total versatility
- * Recommended daily usage up to **8+ hours**



OSPREYDEEPCLEAN®
DRY STEAM CLEANING TECHNOLOGY

SF 10 Accessories

Included with Machine



4m Steam Only
Hose

A03053



400mm Industrial
Lance with Hooked
Nozzle
Requires A03150
A03125



900mm Industrial
Lance with Hooked
Nozzle
Requires A03150
A03131



10kw Steel Tip for
Industrial Lances

A03149



350mm Industrial
Squeegee

A03133



Nylon Detail
Brush

A03081



60mm Round
Nylon Brush

A03074



Copper Detail
Brush

A03082



60mm Round
Copper Brush

A03075



Stainless Steel
Detail Brush

A03083



60mm Round
Stainless Steel
Brush

A03076



55mm Scotch
Brite Round
Pad

A03145



Safety Goggle

A00096



Safety Gloves

A00097

Optional Accessories



3m Steam Hose A03059
6m Steam Hose A03228
13m Steam Hose A03222
16m Steam Hose A03196



"Cleaning in Progress"
Sign

A00972



Accessory Bag

A00903

Technical Details

Power Supply	400 V 50 Hz 16 Amp
Maximum Power	10,000 Watt
Steam Pressure	10 Bar nominal
Boiler Capacity	6 Litres
Boiler Material	RVS AISI 304
Maximum Boiler Temperature	185 °C
Detergent Capacity	2 x 5 Litres
Vacuum / Vacuum Tank Capacity	<i>Optional</i> 1,200 Watt / 10 Litres
Heating Up Time	Approximately 7 Minutes
Machine Dimensions (WxDxH)	57cm x 89cm x 104cm
Cable Length	4 Metres
Net Weight	56 kg
Shipping Weight	108 kg inc. Accessories
Certification / Marking	CE , IPX4
Autonomy	Continuous Operation
Adjustable Output Regulator	Yes
Indicator for Lack of Water	Yes

CALL US ON
+44 (0) 1242 513 123

FOLLOW US

