

SteamForce

SF Eco



The little machine with the big steam

Introducing the new **OSPREYFRANK** range

- Compact but tough with robust stainless steel body
- Industrial quality steam socket
- Professional with continuous boiler refill
- External detergent facility for ease of change
- Steam volume regulator
- Front locking castors
- Simple and clear operation
- Cost effective and environmentally friendly
- Ideal for small areas with no vacuum requirement
- Also available in 120v version



Machine Ordering Codes
230v: M6054
120v: M6053

+44 (0) 1242 513123
www.ospreydc.com

SF Eco Machine Specification

Power Supply	230v 50Hz 13Amp / 120v 60Hz 14Amp	Cable Length	4 metres
Maximum Power	3,000 Watt 1,700 Watt	Machine Dimensions (W x D x H) cm	37cmx82.5cmx100cm
Steam Pressure	6 Bar nominal	Net Weight	25Kg
Boiler Capacity / Material	2.3 Litres / RVS AISI 304	Shipping Weight	32Kg
Detergent Capacity	2 x 5 Litre	Certification/Marking	CE, IPX4
Heating Up Time	Approx. 5 minutes	Max. Boiler Temperature	160°C
Steam production	60 gr./min	Adjustable Output Regulator	Yes
Autonomy	Continuous Operation	Indicator for Lack of Water	Yes

SF Eco Standard Steam Only Accessories

	Steam only Hose 2.5m A03056		Extension Tubes A03060
	Floor Tool A03061	Image to follow	Brush Adaptor for floor tool A03062
	Cover for Floor Tool A03071		Large Triangular Brush A03072
	Squeegee Tool 24cm A03063		Short curved nozzle A03069
	Long nozzle A03065		Nylon Detail Brush A03081
	Copper Detail Brush A03082		Stainless Steel Detail Brush A03083
	50mm Round Nylon Brush A03074		Cotton Cloth A03028



OSPREYDEEPCLEAN
STEAM CLEANING TECHNOLOGY

Unit 41, Central Way, Cheltenham Trade Park, Cheltenham, GL51 8LX

T: +44 (0) 1242 513 123 F: +44 (0) 1242 518 666

E: info@ospreydc.com W: www.ospreydc.com

© 2012 OspreyDeepclean Ltd

No part of this publication should be reproduced, duplicated or be made public in any form whether electronically or otherwise without the express prior permission of OspreyDeepclean Ltd.